



Smart  
connections.

Data sheet

PIKO 12

12

# Technical data PIKO 12



- 3-phase feed-in
- Transformerless converting
- Integrated electronic DC switch
- Broad input voltage range
- Standard integrated communication package with data logger, web server, solar portal and the following interfaces: 2x Ethernet, RS485, S0, 4x analogue inputs (e.g. for ripple control receivers or PIKO Sensor)
- PIKO BA Sensor can be connected for the measurement of building consumption and for dynamic active power control
- Integrated switch contact for self-consumption optimisation
- Smart Home-ready, EEBus 1.0-ready

## Input side (DC)

Max. PV power ( $\cos \varphi = 1$ )	kWp	12.9
Rated input voltage ( $U_{DC,r}$ )	V	680
Max. input voltage ( $U_{DC,max}$ )	V	1000
Min. input voltage ( $U_{DC,min}$ )	V	160
Start-up input voltage ( $U_{DC,start}$ )	V	180
Max. MPP voltage ( $U_{MPP,max}$ )	V	800
Min. MPP voltage for DC rated output in single tracker mode ( $U_{MPP,min}$ )	V	626
Min. MPP voltage for DC rated output in two-tracker mode ( $U_{MPP,min}$ )	V	sym: 345 / 345 asym: 490 / 250
Max. input current ( $I_{DC,max}$ )	A	sym: 18 / 18 asym: 20 / 10
Max. input current with parallel connection	A	18 / 18
Number of DC inputs		2
Number of independent MPP trackers		2

## Output side (AC)

Rated output, $\cos \varphi = 1$ ( $P_{AC,r}$ )	kW	12
Max. output apparent power, $\cos \varphi, adj$	kVA	12
Max. output voltage ( $U_{AC,max}$ )	V	264
Min. output voltage ( $U_{AC,min}$ )	V	185
Rated output current	A	17.4
Max. output current ( $I_{AC,max}$ )	A	19.3
Short-circuit current (peak / RMS)	A	27.4 / 16.7
Grid connection		3 / N / PE, AC, 400V
Rated frequency ( $f_r$ )	Hz	50
Max. grid frequency ( $f_{max}$ )	Hz	51.5
Min. grid frequency ( $f_{min}$ )	Hz	47.5
Setting range of the power factor $\cos \varphi_{AC,r}$		0,80...1...0,80
Power factor for rated power ( $\cos \varphi_{AC,r}$ )		1
Max. total harmonic distortion	%	3

## Device properties

Max. total night-time consumption (own requirements standby)	W	1.8
Max. night-time consumption of communication board	W	1.7

## Efficiency

Max. efficiency	%	97.7
European efficiency	%	97.1
MPP adjustment efficiency	%	99.9

## Warranty

Warranty (years)		5
Warranty extension optional (years)		10 / 20


## System data

Topology: Without galvanic separation - transformerless		✓
Internal protection according to IEC 60529		IP 55
Protective class according to IEC 62103		I
Overvoltage category according to IEC 60664-1 Input side (PV generator)		II
Overvoltage category according to IEC 60664-1 Output side (grid connection)		III
Degree of contamination		3
Environmental category (outdoor installation)		✓
Environmental category (interior installation)		✓
UV resistance		✓
Minimum cable cross-section of AC connecting line	mm <sup>2</sup>	4
Minimum cable cross-section of DC connecting line	mm <sup>2</sup>	4
Min. fusing on output side		B25, C25
Operator protection (EN 62109-1)		RCCB type B
Electronic disconnection device integrated		✓
Height	mm	445 (17.52 in)
Width	mm	580 (22.83 in)
Depth	mm	248 (9.76 in)
Weight	kg	37.5 (82.67 lb)
Cooling principle - convection		-
Cooling principle - regulated fans		✓
Max. air throughput	m <sup>3</sup> /h	2x48
Noise emission	dBA	44
Ambient temperature	°C	-20...60 (-4...140 °F)
Max. installation altitude above sea level	m	2000 (6562 ft)
Relative humidity	%	4...100
Connection technology at input side - MC 4		✓
Connection technology at output side - spring-loaded terminal strip		✓

## Interfaces

Ethernet RJ45		2
RS485		1
S0		1
Analogue inputs		4
PIKO BA Sensor Interface		1

## Efficiency characteristics of PIKO 12



Smart connections.

## Contact

KOSTAL Solar Electric GmbH  
 Hanferstr. 6  
 79108 Freiburg i. Br.  
 Germany  
 Tel. +49 761 477 44 - 100  
 Fax +49 761 477 44 - 111  
 www.kostal-solar-electric.com