

Tiger Pro 72HC

550-570 Watt

MONO-FACIAL MODULE

P-Type

Positive power tolerance of 0~+3%


IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational health and safety management systems



MBB HC Technology

Key Features



Multi Busbar Technology

Better light trapping and current collection to improve module power output and reliability.



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



Reduced Hot Spot Loss

Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).




Longer Life-time Power Yield

0.55% annual power degradation and 25 year linear power warranty.



LINEAR PERFORMANCE WARRANTY





12 Year Product Warranty

25 Year Linear Power Warranty

0.55% Annual Degradation Over 25 years

Engineering Drawings




Packaging Configuration

(Two pallets = One stack)

31 pcs/pallets, 62 pcs/stack, 620 pcs/ 40'HQ Container

Electrical Performance & Temperature Dependence



Mechanical Characteristics

Cell Type	P type Mono-crystalline
No. of cells	144 (6×24)
Dimensions	2278×1134×35mm (89.53×44.65×1.38 inch)
Weight	27 kg (61.73 lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Output Cables	TUV 1×4.0mm ² (+): 400mm, (-): 200mm or Customized Length

SPECIFICATIONS

Module Type	JKM550M-72HL4		JKM555M-72HL4		JKM560M-72HL4		JKM565M-72HL4		JKM570M-72HL4	
	JKM550M-72HL4-V	JKM555M-72HL4-V	JKM555M-72HL4-V	JKM555M-72HL4-V	JKM560M-72HL4-V	JKM560M-72HL4-V	JKM565M-72HL4-V	JKM565M-72HL4-V	JKM570M-72HL4-V	JKM570M-72HL4-V
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	550Wp	409Wp	555Wp	413Wp	560Wp	417Wp	565Wp	420Wp	570Wp	424Wp
Maximum Power Voltage (Vmp)	40.90V	38.42V	40.99V	38.59V	41.09V	38.69V	41.21V	38.74V	41.34V	38.84V
Maximum Power Current (Imp)	13.45A	10.65A	13.54A	10.70A	13.63A	10.77A	13.71A	10.85A	13.79A	10.92A
Open-circuit Voltage (Voc)	49.62V	46.84V	49.72V	46.93V	49.82V	47.02V	49.93V	47.13V	50.04V	47.23V
Short-circuit Current (Isc)	14.03A	11.33A	14.12A	11.40A	14.21A	11.48A	14.30A	11.55A	14.39A	11.62A
Module Efficiency STC (%)	21.29%		21.48%		21.68%		21.91%		22.07%	
Operating Temperature(°C)	-40°C~+85°C									
Maximum system voltage	1000/1500VDC (IEC)									
Maximum series fuse rating	25A									
Power tolerance	0~+3%									
Temperature coefficients of Pmax	-0.35%/°C									
Temperature coefficients of Voc	-0.28%/°C									
Temperature coefficients of Isc	0.048%/°C									
Nominal operating cell temperature (NOCT)	45±2°C									

*STC: Irradiance 1000W/m²

Cell Temperature 25°C

AM=1.5

NOCT: Irradiance 800W/m²

Ambient Temperature 20°C

AM=1.5

Wind Speed 1m/s