

Three Phase Inverter with Synergy Technology USA Domestic Content Eligible*

For North America

SE50KUS / SE80KUS / SE100KUS / SE110KUS / SE120KUS

INVERTER



SOLAREEDGE'S USA-MANUFACTURED OFFERING FOR C&I ROOFTOPS AND CARPORTS

- / Eligible for domestic content*: SolarEdge USA-manufactured inverters, when paired with certain SolarEdge USA-manufactured power optimizers, are intended to be eligible for the enhanced federal income tax credit for domestic content
- / Pre-commissioning feature for automated validation of system components and wiring during the site installation process and prior to grid connection
- / Easy two-person installation with lightweight, modular design (each inverter consists of two or three Synergy units and one Synergy Manager)
- / Independent operation of each Synergy unit enables higher uptime and easy serviceability
- / Built-in thermal sensors detect faulty wiring, ensuring enhanced protection and safety
- / Built-in arc fault protection and rapid shutdown
- / Built-in PID mitigation for maximized system performance
- / Monitored** and field-replaceable surge protection devices, to better withstand surges caused by lightning or other events
- / Built-in module-level monitoring with Ethernet or cellular communication for full system visibility

* Manufactured by SolarEdge with the intent to be eligible for inclusion under the elective safe harbor in calculating the Domestic Content Percentage under the "Rooftop (MLPE)" category (under IRS Notice 2024-41). The PCBA, Electrical Parts, and Enclosure are domestically manufactured to meet the requirements of eligibility to be considered for the ITC domestic content bonus adder. SolarEdge does not provide tax and/or legal advice. You should consult with your own legal and/or tax advisor(s) regarding the eligibility of your project for the ITC or PTC, including the 10% domestic content bonus, to determine how the applicable rules apply to your particular project. The forward-looking statements in this datasheet are accurate as of the date herein and are subject to change. For more information, please contact your local SolarEdge sales representative.

** Applicable only for DC and AC SPDs.

solaredge.com

solaredge

/ Three Phase Inverter with Synergy Technology

USA Domestic Content Eligible for North America

SE50KUS / SE80KUS / SE100KUS / SE110KUS / SE120KUS

Applicable to inverters with part numbers Model Number	SE-DBL- USxxIBNxx	SE-TRI-USxxIBNxx				UNITS
	SE80KUS	SE50KUS	SE100KUS	SE110KUS	SE120KUS	
OUTPUT						
Total Rated AC Output Capacity	80,000	120,000				W
Rated AC Active Output Power	80,000	50,000	100,000	110,000	120,000	W
Maximum AC Apparent Output Power	80,000	50,000	100,000	120,000	120,000	VA
AC Output Line Connections	3W + PE, 4W + PE					
Supported Grids	WYE; TN-C; TN-S; TN-C-S; TT, IT; Delta: IT					
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-N)	244 – 277 – 305	105 – 120 – 132.5	244 – 277 – 305			Vac
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-L)	422.5 – 480 – 529	183 – 208 – 229	422.5 – 480 – 529			Vac
AC Frequency Minimum-Nominal-Maximum ⁽¹⁾	59.5 – 60 – 60.5					Hz
Maximum Continuous Output Current (per phase, PF=1)	96.5	139.5	120	144.3		Aac
GFDI Threshold	1					A
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes					
Total Harmonic Distortion	≤ 3					%
Power Factor Range	±0.85 to 1					
INPUT⁽²⁾						
Maximum DC Power (Module STC) Inverter / Synergy Unit	140,000 / 70,000	87,500 / 29,165	175,000 / 58,300	210,000 / 70,000		W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage DC+ to DC-	1000	600	1000			Vdc
Operating Voltage Range	850 – 1000	370 – 600	850 – 1000			Vdc
Maximum Input Current	2 x 48.25	3 x 46.5	3 x 40	3 x 48.25		Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	167kΩ sensitivity per Synergy Unit ⁽³⁾					
CEC Weighted Efficiency	98.5	97	98.5			%
Nighttime Power Consumption	< 8	< 12				W
ADDITIONAL FEATURES						
Supported Communication Interfaces ⁽⁴⁾	2 x RS485; Ethernet; Wi-Fi (optional); Cellular (optional)					
Smart Energy Management	Export Limitation					
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi access point for local connection					
Arc Fault Protection	Built-in, user configurable (according to UL 1699B)					
Photovoltaic Rapid Shutdown System	NEC 2014 – 2023, built-in, if paired with C651U					
PID Rectifier	Nighttime, built-in					
RS485 Surge Protection (ports 1+2)	Type II, field replaceable, integrated					
AC, DC Surge Protection	Type II, field replaceable, integrated					
DC SAFETY SWITCH						
DC Disconnect	Built-in					
STANDARD COMPLIANCE						
Safety	UL 1699B; UL 1741; UL 1741 SA; UL 1741 SB; UL 1998; CSA C22.2#107.1; Canadian AFCI according to T.I.L. M-07					
Grid Connection Standards	IEEE 1547-2018, Rule 21, Rule 14 (HI)					
Emissions	FCC Part 15 Class A					

(1) For other regional settings please contact SolarEdge support.

(2) For compatibility of inverters and power optimizers, see this [technical note](#).

(3) Where permitted by local regulations.

(4) For specifications of the optional communication options, visit the [Communication product page](#) or the [Knowledge Center](#) to download the relevant product datasheet.

/ Three Phase Inverter with Synergy Technology

USA Domestic Content Eligible for North America

SE50KUS / SE80KUS / SE100KUS / SE110KUS / SE120KUS

Applicable to inverters with part numbers Model Number		SE-DBL- USxxIBNxx	SE-TRI-USxxIBNxx			UNITS
		SE80KUS	SE50KUS	SE100KUS	SE110KUS	
INSTALLATION SPECIFICATIONS						
Number of Synergy Units per Inverter		2	3			
AC Maximum Conduit Size		2 ½"				in
AC Maximum Conductor Size Line / PE		4/0 AWG / 1/0 AWG				
DC Maximum Conduit Size		1 x 3"; 2 x 2"				in
Inverter Unit / Synergy Manager	Multi-input (fuse-less) ⁽⁵⁾ (SE-xxx-USxxlxxSx)	6 / 3 pairs; 6 – 12 AWG	9 / 3 pairs; 6 – 12 AWG			
	Combined input (fuse-less) (SE-xxx-USxxlxxWx)	2 pairs / 1 pair, 2 – 4 AWG; copper or aluminum	3 pairs / 1 pair, 2 – 4 AWG; copper or aluminum			
Dimensions (H x W x D)		Synergy Unit: 22 x 12.9 x 10.75 / 558 x 328 x 273 Synergy Manager: 14.17 x 22.4 x 11.6 / 360 x 560 x 295				in / mm
Weight		Synergy Unit: 70.4 / 32 Synergy Manager: 39.6 / 18				lb / kg
Operating Temperature Range		-40 to +140 / -40 to +60 ⁽⁶⁾				°F / °C
Cooling		Fan (user replaceable)				
Noise		< 67				dBA
Protection Rating		NEMA 3R				
Mounting		Brackets provided				


(5) Fusing is not included with the multi-input version of the Synergy Manager.

(6) For power derating information, see the [Temperature Derating](#) technical note for North America.

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.

-  SolarEdge
-  @SolarEdgePV
-  @SolarEdgePV
-  SolarEdgePV
-  SolarEdge
-  www.solaredge.com/corporate/contact

solaredge.com

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: February 10, 2025 DS-000240-NAM Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.



solaredge